

Intelligent and reliable

Bringing new intelligence to your document processes, this A3 black and white MFP has a colour touchscreen panel that simplifies operation and supports cloud integration.

Intelligent workflow tools

- Intuitive user interface
- Downloadable Smart apps
- Cloud integration
- Smartphone connection

The Smart Operation Panel plays host to a suite of intelligent workflow tools. Downloadable apps, such as ID Card Copy, automate time-consuming processes. Users can connect seamlessly to the MFP and print from / scan to their smartphones and tablets. And, with easy cloud integration, they can scan documents and upload them to cloud services, like DropBox[™] and Sharepoint[™].

Versatile and productive

- Fast 27 ppm print speed
- High capacity ARDF
- A6 to A3 paper formats
- 1600 sheet max capacity

Designed for use in demanding environments, the IM 2702 delivers robust performance with minimal support. Localisation is easy as the MFP supports a variety of languages, including Arabic. And, with pre-set developer and a user replaceable photo conductor unit, it can easily be installed and maintained by local staff. What is more, to ensure a fast return on the initial cost, the MFP's smart energy saving features and high yield toner cartridges reduce running costs.



The IM 2702 provides a versatile and productive answer to all document needs. It prints and copies in black and white, and scans in colour. Fax is an option. The ARDF quickly scans double-sided originals and multipage documents are printed at speed. With up to three 500 sheet paper trays and a multi-sheet bypass on line, it is easy to print onto different paper sizes or to feed envelopes and labels. And, with the MFP switching seamlessly between trays, there really is no need to stop.

Easy to maintain

- User installable MFP
- User replaceable Photo Conductor Unit
- Multiple language support
- High yield toner



RICOH IM 2702

MAIN SPECIFICATIONS

One-bin tray

GENERAL		
Warm-up time	25 seconds	
irst output speed: B/W	6.5 seconds	
Continuous output speed	27 ppm	
lemory: standard	2 GB	
lemory: maximum	2 GB	
RDF capacity	100 sheets	
Veight	46.5 kg	
Dimensions: W x D x H	587 x 581 x 677 mm	
Power source	220 - 240 V, 50 - 60 Hz	
aser classification	Class 1 Laser Product (IEC60825 - 1:2014)	
COPIER		
Aultiple copying	Up to 999 copies	
Resolution	600 x 600 dpi	
oom	From 25% to 400%	
RINTER		
	PCL5e	
Printer language	PCL5e PCL6	
	PostScript 3 (emulation)	
rint resolution: maximum	600 x 600 dpi	
letwork interface: standard	Ethernet 10 base-T/100 base-TX/1000 base-T	
	USB2.0 Type B	
	Wireless LAN (IEEE 802.11 alb/g/n)	
tabile printing conchility	USB Host 2.0	
Nobile printing capability	Apple AirPrint Mopria®	
	Google Cloud Print	
etwork protocol	TCP/IP (IP v4, IP v6)	
/indows® environments	Windows® 7	
	Windows® 8.1	
	Windows® 10	
	Windows® Server 2008	
	Windows® Server 2008R2	
	Windows® Server 2012	
	Windows® Server 2012R2	
	Windows® Server 2016	
lac OS environments	Windows® Server 2019 Macintosh OS X v10.8 - v10.11	
CANNER		
Scanning: B/W	50 ipm	
canning: full colour	50 ipm	
Resolution: maximum	1,200 dpi	
undled drivers	Network TWAIN	
AX		
compatibility	ITU-T (CCITT) G3	
ransmission speed	3 seconds	
lodem speed: maximum	33.6 Kbps	
APER HANDLING		
Recommended paper size	Bypass tray: Custom Size paper (Width, Length) Duplex tray:	
Paper input: standard	500 sheets	
aper input: maximum	1,600 sheets	
aper output: standard	250 sheets	
aper weight	250 sheets Trays: 52 - 105 g/m ²	
aper weight	Bypass: 52 - 105 gm²	
COLOGY		
ower consumption: max.	Less than 1,550 W	
Power consumption operation: 3&W	500 W	
OUTPUT TRAYS AND FINISHER OPTIONS		
x 500-sheet paper tray		
x 500-sheet paper tray		
Dne-bin tray		

RICOH IM 2702

MAIN SPECIFICATIONS


OTHER OPTIONS

Fax unit ADF handle NFC card reader Bypass tray cover

CONSUMABLES

Toner (regular yield) Toner (high yield) Consumable yield based on 2p/j 6% coverage on A4 4,000 prints 12,000 prints

Ricoh Europe (Netherlands) B.V. "Nieuw Kronenburg" Prof. W.H. Keesomlaan 1 1183 DJ Amstelveen



+31 (0)20 5774111



The Netherlands

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2022 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.



